

COMPRESSOR DEFINITION

Designation	ES X55CBC
Nominal Voltage/Frequency	115-127 V 60 Hz
Engineering Number	518102628

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	115-127 / 60	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	-	103 to 140 V
8.2 LBP (43°C Ambient temperature)	Static	-	103 to 140 V
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	6.9	[kgf/cm ²] (98 psig)	/ °C - °F
9.2 Peak	7.8	[kgf/cm ²] (111 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/5	[hp]
2 Displacement	7.87	[cm ³] (0.480 cu.in)
2.1 Bore [mm]	22.500	
2.2 Stroke [mm]	19.800	
3 Lubricant charge	115	[ml] (3.89 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO5	
4 Weight (with oil charge)	5.2	[kg] (11.46 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELECTRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115-127 V 60 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	8EA14C83	
3 Start capacitor	-	[μF(VAC minimum)]
4 Run capacitor	12(180)	[μF(VAC minimum)]
5 Motor protection	4TM319KFBYY-53	
6 Start winding resistance	8.09	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	7.23	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	7.91	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	2.11	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	2.30	[A] - Measured according to UL 984
11 Approval boards certification	NOM - UL	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @115V60Hz			GEALBP Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 40.5°C (104.9°F)	
Cooling capacity (Qe) +/- 5%			Input power (We) +/- 5%	Electric current +/- 5%	Mass flow rate +/- 5%	Efficiency EER & COP +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
614	155	180	89	0.80	1.93	6.89	1.74	2.02

E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V60Hz		GEA Static			(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity (Qe) +/- 5%			Input power (We) +/- 5%	Electric current +/- 5%	Mass flow rate +/- 5%	Efficiency EER & COP +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	337	85	99	65	0.58	0.00	5.21	1.31	1.53
-30	(-22)	449	113	131	74	0.66	0.00	6.08	1.53	1.78
-25	(-13)	585	147	171	83	0.75	0.00	7.04	1.77	2.06
-20	(- 4)	747	188	219	92	0.83	0.00	8.09	2.04	2.37
-15	(+ 5)	937	236	275	102	0.91	0.00	9.23	2.33	2.70
-10	(+14)	1158	292	339	111	0.99	0.00	10.48	2.64	3.07

TEST CONDITIONS: @115V60Hz		GEA Static			(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity (Qe) +/- 5%			Input power (We) +/- 5%	Electric current +/- 5%	Mass flow rate +/- 5%	Efficiency EER & COP +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	306	77	90	66	0.59	0.00	4.67	1.18	1.37
-30	(-22)	415	105	122	76	0.68	0.00	5.45	1.37	1.60
-25	(-13)	549	138	161	87	0.78	0.00	6.27	1.58	1.84
-20	(- 4)	710	179	208	99	0.89	0.00	7.14	1.80	2.09
-15	(+ 5)	901	227	264	111	1.00	0.00	8.07	2.03	2.36
-10	(+14)	1122	283	329	124	1.11	0.00	9.07	2.29	2.66

TEST CONDITIONS: @115V60Hz		GEA Static			(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity (Qe) +/- 5%			Input power (We) +/- 5%	Electric current +/- 5%	Mass flow rate +/- 5%	Efficiency EER & COP +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	279	70	82	65	0.59	0.00	4.26	1.07	1.25
-30	(-22)	382	96	112	77	0.69	0.00	4.97	1.25	1.46
-25	(-13)	512	129	150	90	0.81	0.00	5.68	1.43	1.66
-20	(- 4)	670	169	196	105	0.94	0.00	6.40	1.61	1.87
-15	(+ 5)	857	216	251	120	1.08	0.00	7.14	1.80	2.09
-10	(+14)	1076	271	315	136	1.22	0.00	7.92	2.00	2.32

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard ES/FMS		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 45° up		
3.2 DISCHARGE	5.1 +0.10/+0.00	[mm]	(0.201" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted 45° up		
3.3 PROCESS	6 +0.08/-0.08	[mm]	(0.236" +0.003"/-0.003")
3.3.1 Material	Copper(OD)		
3.3.2 Shape	Slanted 45° up		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		