

COMPRESSOR DEFINITION

Designation	NE U6217U
Nominal Voltage/Frequency	208-230 V 60 Hz
Engineering Number	863JD92

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-290		
3 Nominal voltage and frequency	208-230 / 60	[V / Hz]	
4 Application type	Medium Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-20°C to 10°C	(-4°F to 50°F)	
5 Motor type	CSCR		
6 Starting torque	HST - Hight starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	18.4	[kgf/cm ²] (262 psig)	/ °C - °F
9.2 Peak	20.6	[kgf/cm ²] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	3/4	[hp]
2 Displacement	14.28	[cm ³] (0.871 cu.in)
2.1 Bore [mm]	30.157	
2.2 Stroke [mm]	20.000	
3 Lubricant charge	350	[ml] (11.84 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	AB / ISO32	
4 Weight (with oil charge)	11.56	[kg] (25.49 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELECTRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	208-230 V 60 Hz 1~ (Single phase)	
2 Starting device type	Voltage Relay	
2.1 Starting device	RVA4AH3C-648	
3 Start capacitor	108-130(330)	[µF(VAC minimum)]
4 Run capacitor	12.5(400)	[µF(VAC minimum)]
5 Motor protection	MRA38168-3261	
6 Start winding resistance	9.27	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	3.39	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	29.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	5.00	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	UL	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @208V60Hz			ASHRAEHBP46 Fan		Evaporating temperature (Condensing temperature		7.2°C (44.96°F) 54.4°C (129.92°F)	
Cooling capacity (Qe) +/- 5%			Input power (We) +/- 5%	Electric current +/- 5%	Mass flow rate +/- 5%	Efficiency EER & COP +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
7992	2014	2342	890	4.42	27.35	8.98	2.26	2.63

E - PERFORMANCE - CURVES

TEST CONDITIONS: @208V60Hz			ASHRAE46 Fan		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity (Qe) +/- 5%			Input power (We) +/- 5%	Electric current +/- 5%	Mass flow rate +/- 5%	Efficiency EER & COP +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	3751	945	1099	495	2.50	10.59	7.57	1.91	2.22
-15	(+ 5)	4558	1149	1336	535	2.69	12.91	8.53	2.15	2.50
-10	(+14)	5524	1392	1619	576	2.89	15.71	9.60	2.42	2.81
-5	(+23)	6650	1676	1949	617	3.09	19.01	10.78	2.72	3.16
0	(+32)	7936	2000	2325	659	3.29	22.81	12.04	3.03	3.53
+5	(+41)	9381	2364	2749	701	3.50	27.14	13.37	3.37	3.92
+10	(+50)	10985	2768	3219	745	3.71	32.01	14.76	3.72	4.32

TEST CONDITIONS: @208V60Hz			ASHRAE46 Fan		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity (Qe) +/- 5%			Input power (We) +/- 5%	Electric current +/- 5%	Mass flow rate +/- 5%	Efficiency EER & COP +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	3315	835	971	532	2.66	10.11	6.23	1.57	1.83
-15	(+ 5)	4061	1023	1190	582	2.90	12.44	6.98	1.76	2.05
-10	(+14)	4945	1246	1449	632	3.14	15.22	7.83	1.97	2.29
-5	(+23)	5968	1504	1749	682	3.38	18.46	8.75	2.21	2.56
0	(+32)	7129	1796	2089	731	3.63	22.18	9.75	2.46	2.86
+5	(+41)	8427	2124	2469	781	3.87	26.41	10.79	2.72	3.16
+10	(+50)	9864	2486	2890	831	4.12	31.15	11.87	2.99	3.48

TEST CONDITIONS: @208V60Hz			ASHRAE46 Fan		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity (Qe) +/- 5%			Input power (We) +/- 5%	Electric current +/- 5%	Mass flow rate +/- 5%	Efficiency EER & COP +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	2850	718	835	562	2.82	9.50	5.08	1.28	1.49
-15	(+ 5)	3530	890	1034	625	3.11	11.81	5.65	1.42	1.65
-10	(+14)	4328	1091	1268	687	3.41	14.55	6.29	1.58	1.84
-5	(+23)	5243	1321	1536	749	3.70	17.72	7.00	1.76	2.05
0	(+32)	6274	1581	1839	810	4.00	21.36	7.75	1.95	2.27
+5	(+41)	7423	1871	2175	870	4.30	25.46	8.54	2.15	2.50
+10	(+50)	8688	2189	2546	930	4.60	30.06	9.34	2.35	2.74

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.1 +0.10/+0.00	[mm]	(0.319" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		