

### COMPRESSOR DEFINITION

Designation	NE U2155U
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	862KA58

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-290		
3 Nominal voltage and frequency	220-240 / 50	[ V / Hz ]	
4 Application type	Low Back Pressure R290		
4.1 Evaporating temperature range	-40°C to -10°C	(-40°F to 14°F)	
5 Motor type	CSCR		
6 Starting torque	HST - Hight starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	18.4	[kgf/cm <sup>2</sup> ] (262 psig)	/ °C - °F
9.2 Peak	20.6	[kgf/cm <sup>2</sup> ] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	3/4	[hp]
2 Displacement	13.54	[cm <sup>3</sup> ] (0.826 cu.in)
2.1 Bore [mm]	29.362	
2.2 Stroke [mm]	20.000	
3 Lubricant charge	350	[ml] (11.84 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	AB / ISO32	
4 Weight (with oil charge)	11.1	[kg] (24.47 lb.)
5 Nitrogen charge	-	[kgf/cm <sup>2</sup> ]

### C - ELECTRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	Voltage Relay	
2.1 Starting device	RVA4L3C-566	
3 Start capacitor	64-77(330)	[µF(VAC minimum)]
4 Run capacitor	5(400)	[µF(VAC minimum)]
5 Motor protection	T0168/G9	
6 Start winding resistance	19.29	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	5.98	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	17.50	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	2.59	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	CCC - VDE	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Fan		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity (Qe) +/- 5%			Input power (We) +/- 5%	Electric current +/- 5%	Mass flow rate +/- 5%	Efficiency EER & COP +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
2181	550	639	410	2.04	6.49	5.32	1.34	1.56

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE32 Fan		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity (Qe) +/- 5%			Input power (We) +/- 5%	Electric current +/- 5%	Mass flow rate +/- 5%	Efficiency EER & COP +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	1112	280	326	244	1.33	3.28	4.55	1.15	1.33
-35	(-31)	1420	358	416	277	1.46	4.20	5.13	1.29	1.50
-30	(-22)	1814	457	532	310	1.60	5.38	5.85	1.48	1.72
-25	(-13)	2296	579	673	343	1.73	6.83	6.70	1.69	1.96
-20	(- 4)	2864	722	839	375	1.87	8.55	7.63	1.92	2.24
-15	(+ 5)	3519	887	1031	407	2.01	10.54	8.64	2.18	2.53
-10	(+14)	4260	1074	1248	439	2.15	12.82	9.71	2.45	2.84

TEST CONDITIONS: @220V50Hz			ASHRAE32 Fan		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity (Qe) +/- 5%			Input power (We) +/- 5%	Electric current +/- 5%	Mass flow rate +/- 5%	Efficiency EER & COP +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	1034	261	303	254	1.37	3.05	4.07	1.03	1.19
-35	(-31)	1335	336	391	292	1.52	3.95	4.58	1.15	1.34
-30	(-22)	1718	433	503	330	1.68	5.09	5.19	1.31	1.52
-25	(-13)	2183	550	640	369	1.84	6.49	5.90	1.49	1.73
-20	(- 4)	2730	688	800	408	2.01	8.15	6.68	1.68	1.96
-15	(+ 5)	3359	846	984	448	2.19	10.06	7.50	1.89	2.20
-10	(+14)	4070	1026	1193	488	2.37	12.24	8.34	2.10	2.44

TEST CONDITIONS: @220V50Hz			ASHRAE32 Fan		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity (Qe) +/- 5%			Input power (We) +/- 5%	Electric current +/- 5%	Mass flow rate +/- 5%	Efficiency EER & COP +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	953	240	279	260	1.39	2.81	3.67	0.92	1.07
-35	(-31)	1245	314	365	303	1.56	3.68	4.11	1.04	1.20
-30	(-22)	1613	407	473	347	1.75	4.78	4.64	1.17	1.36
-25	(-13)	2059	519	603	393	1.94	6.12	5.24	1.32	1.53
-20	(- 4)	2582	651	757	440	2.15	7.70	5.87	1.48	1.72
-15	(+ 5)	3183	802	933	489	2.37	9.53	6.52	1.64	1.91
-10	(+14)	3860	973	1131	538	2.59	11.61	7.17	1.81	2.10

### F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	Yes		
3 Connectors			
3.1 SUCTION	8.1 +0.10/+0.00	[mm]	(0.319" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	8.1 +0.10/+0.00	[mm]	(0.319" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		