

### COMPRESSOR DEFINITION

Designation	NE U6210U
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	862FA51

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-290		
3 Nominal voltage and frequency	220-240 / 50	[ V / Hz ]	
4 Application type	Medium Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-20°C to 10°C	(-4°F to 50°F)	
5 Motor type	CSIR		
6 Starting torque	HST - Hight starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	18.4	[kgf/cm <sup>2</sup> ] (262 psig)	/ °C - °F
9.2 Peak	20.6	[kgf/cm <sup>2</sup> ] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	1/3	[hp]
2 Displacement	8.77	[cm <sup>3</sup> ] (0.535 cu.in)
2.1 Bore [mm]	26.497	
2.2 Stroke [mm]	15.920	
3 Lubricant charge	350	[ml] (11.84 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	AB / ISO32	
4 Weight (with oil charge)	10.6	[kg] (23.37 lb.)
5 Nitrogen charge	-	[kgf/cm <sup>2</sup> ]

### C - ELECTRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	MTRP-0030	
3 Start capacitor	53-64(330)	[μF(VAC minimum)]
4 Run capacitor	-	[μF(VAC minimum)]
5 Motor protection	MST26ALK-3259	
6 Start winding resistance	27.92	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	4.53	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	20.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	2.90	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	CCC - VDE	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAEHBP46 Fan		Evaporating temperature (Condensing temperature		7.2°C (44.96°F) 54.4°C (129.92°F)	
Cooling capacity (Qe) +/- 5%			Input power (We) +/- 5%	Electric current +/- 5%	Mass flow rate +/- 5%	Efficiency EER & COP +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
4200	1058	1231	463	3.37	14.37	9.07	2.29	2.66

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE46 Fan		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity (Qe) +/- 5%			Input power (We) +/- 5%	Electric current +/- 5%	Mass flow rate +/- 5%	Efficiency EER & COP +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	1845	465	541	295	2.99	5.20	6.25	1.58	1.83
-15	(+ 5)	2295	578	672	314	3.03	6.50	7.31	1.84	2.14
-10	(+14)	2828	713	829	330	3.06	8.05	8.58	2.16	2.51
-5	(+23)	3445	868	1009	343	3.08	9.85	10.06	2.54	2.95
0	(+32)	4145	1045	1215	353	3.11	11.91	11.78	2.97	3.45
+5	(+41)	4929	1242	1444	360	3.13	14.26	13.72	3.46	4.02
+10	(+50)	5796	1461	1698	364	3.14	16.89	15.90	4.01	4.66

TEST CONDITIONS: @220V50Hz			ASHRAE46 Fan		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity (Qe) +/- 5%			Input power (We) +/- 5%	Electric current +/- 5%	Mass flow rate +/- 5%	Efficiency EER & COP +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	1590	401	466	311	2.99	4.85	5.13	1.29	1.50
-15	(+ 5)	1988	501	583	336	3.04	6.09	5.92	1.49	1.73
-10	(+14)	2468	622	723	358	3.09	7.59	6.87	1.73	2.01
-5	(+23)	3028	763	887	378	3.14	9.36	7.99	2.01	2.34
0	(+32)	3669	925	1075	395	3.18	11.41	9.28	2.34	2.72
+5	(+41)	4392	1107	1287	409	3.22	13.76	10.75	2.71	3.15
+10	(+50)	5195	1309	1522	421	3.26	16.41	12.39	3.12	3.63

TEST CONDITIONS: @220V50Hz			ASHRAE46 Fan		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity (Qe) +/- 5%			Input power (We) +/- 5%	Electric current +/- 5%	Mass flow rate +/- 5%	Efficiency EER & COP +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	1343	338	394	328	3.02	4.48	4.07	1.03	1.19
-15	(+ 5)	1683	424	493	358	3.09	5.63	4.72	1.19	1.38
-10	(+14)	2101	529	616	386	3.15	7.06	5.46	1.38	1.60
-5	(+23)	2598	655	761	412	3.21	8.78	6.32	1.59	1.85
0	(+32)	3173	800	930	435	3.27	10.80	7.29	1.84	2.14
+5	(+41)	3827	964	1121	456	3.33	13.13	8.38	2.11	2.46
+10	(+50)	4559	1149	1336	475	3.38	15.77	9.60	2.42	2.81

### F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.1 +0.10/+0.00	[mm]	(0.319" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		