

COMPRESSOR DEFINITION

Designation	NE U6214U
Nominal Voltage/Frequency	115-127 V 60 Hz
Engineering Number	863LE92

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-290		
3 Nominal voltage and frequency	115-127 / 60	[V / Hz]	
4 Application type	Medium Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-20°C to 10°C	(-4°F to 50°F)	
5 Motor type	CSIR		
6 Starting torque	HST - Hight starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	18.4	[kgf/cm ²] (262 psig)	/ °C - °F
9.2 Peak	20.6	[kgf/cm ²] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	3/4	[hp]
2 Displacement	12.11	[cm ³] (0.739 cu.in)
2.1 Bore [mm]	27.775	
2.2 Stroke [mm]	20.000	
3 Lubricant charge	350	[ml] (11.84 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	AB / ISO32	
4 Weight (with oil charge)	11.5	[kg] (25.35 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELECTRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115-127 V 60 Hz 1 ~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	MTRPH-70-31	
3 Start capacitor	243-292(165)	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	T0736/J5	
6 Start winding resistance	5.45	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	0.92	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	42.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	CCC - UL	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @115V60Hz			ASHRAEHBP46 Fan		Evaporating temperature (Condensing temperature		7.2°C (44.96°F) 54.4°C (129.92°F)	
Cooling capacity (Qe) +/- 5%			Input power (We) +/- 5%	Electric current +/- 5%	Mass flow rate +/- 5%	Efficiency EER & COP +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
6787	1710	1989	809	8.41	23.23	8.39	2.11	2.46

E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V60Hz			ASHRAE46 Fan		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity (Qe) +/- 5%			Input power (We) +/- 5%	Electric current +/- 5%	Mass flow rate +/- 5%	Efficiency EER & COP +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	3148	793	922	441	5.75	8.88	7.14	1.80	2.09
-15	(+ 5)	3867	974	1133	478	5.99	10.96	8.09	2.04	2.37
-10	(+14)	4704	1185	1378	515	6.23	13.38	9.14	2.30	2.68
-5	(+23)	5659	1426	1658	551	6.49	16.18	10.27	2.59	3.01
0	(+32)	6734	1697	1973	587	6.75	19.35	11.46	2.89	3.36
+5	(+41)	7928	1998	2323	625	7.03	22.93	12.69	3.20	3.72
+10	(+50)	9241	2329	2708	663	7.32	26.93	13.94	3.51	4.08

TEST CONDITIONS: @115V60Hz			ASHRAE46 Fan		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity (Qe) +/- 5%			Input power (We) +/- 5%	Electric current +/- 5%	Mass flow rate +/- 5%	Efficiency EER & COP +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	2796	704	819	470	5.95	8.53	5.94	1.50	1.74
-15	(+ 5)	3443	868	1009	519	6.26	10.55	6.63	1.67	1.94
-10	(+14)	4197	1058	1230	566	6.57	12.91	7.40	1.87	2.17
-5	(+23)	5057	1274	1482	613	6.90	15.64	8.24	2.08	2.42
0	(+32)	6024	1518	1765	660	7.25	18.74	9.13	2.30	2.67
+5	(+41)	7098	1789	2080	708	7.61	22.24	10.04	2.53	2.94
+10	(+50)	8279	2086	2426	756	7.99	26.15	10.95	2.76	3.21

TEST CONDITIONS: @115V60Hz			ASHRAE46 Fan		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity (Qe) +/- 5%			Input power (We) +/- 5%	Electric current +/- 5%	Mass flow rate +/- 5%	Efficiency EER & COP +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	2390	602	700	499	6.10	7.97	4.79	1.21	1.40
-15	(+ 5)	2981	751	873	558	6.50	9.97	5.34	1.34	1.56
-10	(+14)	3666	924	1074	616	6.92	12.32	5.95	1.50	1.74
-5	(+23)	4445	1120	1302	673	7.36	15.03	6.61	1.67	1.94
0	(+32)	5319	1340	1559	729	7.82	18.10	7.30	1.84	2.14
+5	(+41)	6288	1584	1842	786	8.30	21.57	8.00	2.02	2.34
+10	(+50)	7352	1853	2154	844	8.80	25.44	8.69	2.19	2.55

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.1 +0.10/+0.00	[mm]	(0.319" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		