

COMPRESSOR DEFINITION

Designation	NE U6217U
Nominal Voltage/Frequency	115-127 V 60 Hz
Engineering Number	863JE92

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-290		
3 Nominal voltage and frequency	115-127 / 60	[V / Hz]	
4 Application type	Medium Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-20°C to 10°C	(-4°F to 50°F)	
5 Motor type	CSIR		
6 Starting torque	HST - Hight starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	18.4	[kgf/cm ²] (262 psig)	/ °C - °F
9.2 Peak	20.6	[kgf/cm ²] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	3/4	[hp]
2 Displacement	14.28	[cm ³] (0.871 cu.in)
2.1 Bore [mm]	30.157	
2.2 Stroke [mm]	20.000	
3 Lubricant charge	350	[ml] (11.84 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	AB / ISO32	
4 Weight (with oil charge)	11.6	[kg] (25.57 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELECTRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115-127 V 60 Hz 1 ~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	MTRPH-65-31	
3 Start capacitor	189-227(250)	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	T0873/C9	
6 Start winding resistance	3.81	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	0.96	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	45.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	9.30	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	UL	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @115V60Hz			ARIMBP Fan		Evaporating temperature (Condensing temperature		-6.7°C (19.94°F) 48.9°C (120.02°F)	
Cooling capacity (Qe)			Input power (We)	Electric current	Mass flow rate	Efficiency EER & COP		
+/- 5%			+/- 5%	+/- 5%	+/- 5%	+/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
4302	1084	1261	755	8.06	17.98	5.70	1.44	1.67

E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V60Hz			ARI4 Fan		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity (Qe)			Input power (We)	Electric current	Mass flow rate	Efficiency EER & COP		
		+/- 5%			+/- 5%	+/- 5%	+/- 5%	+/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	3138	791	920	521	6.30	11.07	6.02	1.52	1.76
-15	(+ 5)	3770	950	1105	570	6.64	13.41	6.62	1.67	1.94
-10	(+14)	4576	1153	1341	619	7.00	16.41	7.39	1.86	2.17
-5	(+23)	5554	1400	1628	669	7.37	20.11	8.30	2.09	2.43
0	(+32)	6707	1690	1965	718	7.76	24.54	9.33	2.35	2.73
+5	(+41)	8033	2024	2354	769	8.17	29.76	10.45	2.63	3.06
+10	(+50)	9534	2402	2794	819	8.59	35.79	11.64	2.93	3.41

TEST CONDITIONS: @115V60Hz			ARI4 Fan		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity (Qe)			Input power (We)	Electric current	Mass flow rate	Efficiency EER & COP		
		+/- 5%			+/- 5%	+/- 5%	+/- 5%	+/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	2706	682	793	556	6.53	10.58	4.87	1.23	1.43
-15	(+ 5)	3259	821	955	621	7.01	12.82	5.25	1.32	1.54
-10	(+14)	3974	1001	1164	685	7.50	15.77	5.80	1.46	1.70
-5	(+23)	4852	1223	1422	747	7.99	19.46	6.49	1.63	1.90
0	(+32)	5894	1485	1727	809	8.48	23.94	7.29	1.84	2.14
+5	(+41)	7098	1789	2080	869	8.98	29.23	8.17	2.06	2.40
+10	(+50)	8466	2133	2481	928	9.47	35.39	9.12	2.30	2.67

TEST CONDITIONS: @115V60Hz			ARI4 Fan		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity (Qe)			Input power (We)	Electric current	Mass flow rate	Efficiency EER & COP		
		+/- 5%			+/- 5%	+/- 5%	+/- 5%	+/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	2248	566	659	593	6.77	9.88	3.79	0.95	1.11
-15	(+ 5)	2694	679	789	671	7.37	11.93	4.02	1.01	1.18
-10	(+14)	3292	830	965	746	7.97	14.73	4.41	1.11	1.29
-5	(+23)	4043	1019	1185	818	8.55	18.32	4.94	1.25	1.45
0	(+32)	4946	1246	1449	887	9.13	22.73	5.58	1.41	1.63
+5	(+41)	6001	1512	1758	954	9.70	28.01	6.29	1.59	1.84
+10	(+50)	7209	1817	2112	1019	10.26	34.19	7.07	1.78	2.07

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.1 +0.10/+0.00	[mm]	(0.319" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		