

STANDARD PORTFOLIO FOR UNHOUSED PORTFOLIO

R290 Condensing units Models

Models	Disp. [cc]	Motor type	Performance EN13215 W, RGT20, T. amb 32°C, T. evap. -35°C			Noise dB(A)		Liquid Receiver
			CAP [W]	Consumption [W]	COP [W/W]	Sound Pressure @10m	Sound Power	Internal Volume [L]
UEMC3117U	4.37	RSCR	117	85	1.38	28.8	56.8	0.325
UEMC3119U	4.53	RSCR	140	98	1.43	28.8	56.8	0.325
UEMC3121U	5.19	RSCR	158	108	1.46	29	57	0.325
UEMC3130U	7.32	RSCR	213	149	1.43	35.8	63.8	0.325
UEMX2134U	8.8	CSIR	272	214	1.27	35.7	63.7	0.325
UEMC3140U	9.04	RSCR	280	204	1.37	35.7	63.7	0.325
UNEU2140U	10.39	CSIR	293	241	1.22	35.9	63.9	0.325
UNEU2155U	13.54	CSIR	394	324	1.22	36.3	64.3	0.325
UNEU2170UA	16.8	CSR	492	396	1.24	36.4	64.4	0.325
UNEX2180UB	18,7	CSR	555	427	1.30	36.5	64.5	0.325
UNEX2190U	21.02	CSR	596	475	1.25	36.5	64.5	0.325
UNTX2211U	27.8	CSR	795	613	1.30	37.1	65.1	0.325
UNTX2213U	33.4	CSR	921	720	1.28	39.5	67.5	0.325
UNJX2215U	38	CSR	1000	798	1.25	42.7	70.7	0.49

Models	Disp. [cc]	Motor type	Performance EN13215 W, RGT20, T. amb 32°C, T. evap. -35°C			Noise dB(A)		Liquid Receiver
			CAP [W]	Consumption [W]	COP [W/W]	Sound Pressure @10m	Sound Power	Internal Volume [L]
UEMX6144U	4,5	CSIR	391	183	2.14	35.7	63.7	0.325
UEMX6152U	5,19	CSIR	429	197	2.18	35.8	63.8	0.325
UEMX6165U	6,09	CSIR	492	266	1.85	35	63	0.325
UEMX6181U	7,28	CSIR	578	261	2.21	34.9	62.9	0.325
UEMX6210U	8,77	CSIR	684	376	1.82	34.9	62.9	0.325
UNEU6212U	10	CSR	848	427	1.99	36.1	64.1	0.325

UNEU6214U	12,11	CSR	1003	484	2.07	36	64	0.325
UNEX6217U	14,28	CSIR	1126	574	1.96	36	64	0.325
UNEU6220U	16,8	CSR	1330	655	2.03	36.5	64.5	0.325
UNEX6222U	18,7	CSR	1489	680	2.19	30.9	58.9	0.49
UNEX6225U	21,02	CSR	1738	787	2.21	32.8	60.8	0.49
UNTX6233U	27,8	CSR	2182	1013	2.15	38.7	66.7	0.49
UNTX6238U	33,4	CSR	2655	1288	2.06	39.5	67.5	0.49
UNJX6244U	38	CSR	2821	1461	1.93	42.7	70.7	0.49

Models	RPM	Disp. [cc]	Performance EN13215 W, RGT20, T. amb 32°C, T. evap. -35°C			Performance EN13215 W, RGT20, T. amb 32°C, T. evap. -10°C			Liquid Receiver
			CAP [W]	Consumption [W]	COP [W/W]	CAP [W]	Consumption [W]	COP [W/W]	Internal Volume [L]
UFMFT406U	4500rpm	6,44	249	208	1.20	746	386	1.93	0.32
	3000rpm		182	132	1.38	574	220	2.61	
	1400rpm		88	65	1.35	298	97	3.07	
UFMFT408U	4000rpm	7,95	330	238	1.39	871	399	2.18	0.32
	3600rpm		296	208	1.42	818	361	2.27	
	1800rpm		143	102	1.40	424	159	2.67	
UFMFT411U	4500rpm	11,14	460	352	1.31	1361	601	2.26	0.32
	3000rpm		369	231	1.60	1051	383	2.74	
	1800rpm		223	146	1.53	640	222	2.88	
UFMFD413U	4500rpm	10,85	485	346	1.40	1315	620	2.12	0.32
	3600rpm		406	274	1.48	1113	464	2.40	
	1800rpm		201	148	1.36	586	224	2.62	
UFMFT415U	4500rpm	14,77	646	472	1.37	1543	834	1.85	0.4
	3600rpm		486	386	1.26	1362	729	1.87	
	1600rpm		260	182	1.43	776	313	2.48	

Models	Disp. [cc]	Motor type	Performance EN13215 W, RGT20, T. amb 32°C, T. evap. -35°C			Noise dB(A)		Liquid Receiver
			CAP [W]	Consumption [W]	COP [W/W]	Sound Pressure @10m	Sound Power	Internal Volume [L]
UEMC3117UEAE08	3,97	RSCR	117	85	1.38	28.8	56.8	0,08
UEMC3119UEAE08	4,53	RSCR	140	98	1.43	28.8	56.8	0,08
UEMC3121UEAE08	5,19	RSCR	165	112	1.47	29	57	0,08
UEMC3130UEAE08	6,92	RSCR	208	140	1.49	29.4	57.4	0,08
UEMX2134UEAE08	8,8	CSIR	251	208	1.21	29.6	57.6	0,08
UEMC3140UEAE08	9,04	RSCR	278	194	1.43	30	58	0,13
UNEU2140UEAE08	9,99	CSIR	283	229	1.24	31	59	0,22
UNEU2155UEAE08	13,54	CSIR	361	329	1.10	32	60	0,22

Models	Disp. [cc]	Motor type	Performance EN13215 W, RGT20, T. amb 32°C, T. evap. -10°C			Noise dB(A)		Liquid Receiver
			CAP [W]	Consumption [W]	COP [W/W]	Sound Pressure @10m	Sound Power	Internal Volume [L]
UEMX6144UEAE08	4,5	CSIR	383	175	2.19	31	60	0,13
UEMX6152UEAE08	5,19	CSIR	414	200	2.07	31	60	0,13
UEMX6165UEAE08	6,09	CSIR	489	235	2.08	32	61	0,22
UEMX6181UEAE08	7,28	CSIR	554	258	2.15	33	62	0,22